NORMACLAMP® – Hose Clamps

NORMACLAMP® TORRO® – Worm Drive Hose Clips to DIN 3017

NORMACLAMP® TORRO® hose clips are specially suitable for applications under high mechanical loads. Since we are contin-

uously working to improve its features this clip is still setting standards for modern hose clip design.

The distinguishing feature of the NORMACLAMP® TORRO® is the asymmetrical construction which tells you at first sight whether it is a genuine TORRO® or not.

Short description of technical features



- 1 Improved asymmetric housing = even distribution of forces and safe assembly
- 2 Screw support = Ease of assembly due to the safe guidance of the emerging band end
- 3 Material and clamping range stamped on the band = prevention of errors
- 4 Asymmetric extension = prevents the housing from tilting over when the clamp is tightened
- **5** Short housing saddle = even contact pressure = improved efficiency
- **6** Smooth or stamped inside of band = optimal hose protection

Materials

W1*	W2*	W3	W4	W5
Х	Х	Х	Х	Х

^{*} No chromium VI used for the coating of the closure components

NORMACLAMP® – Hose Clamps

Types of clamp band





Band width 9 mm

- W1 with smooth inside
- W2, W3, W4, W5 with stamped inside

Band width 12 mm

- W1, W2, W3 with smooth inside
- W4, W5 with stamped inside

Screw





		W1	W2	W3	W4	W5
Phillips head	SW 7*	•	•			
Slotted head	SW 7**			•	•	•

* Band width 7.5 mm = SW 6

** Band width 16 mm = SW 8

The advantages at a glance

- Multi-range hose clamp
- Material: W1, W2, W3, W4, W5
- Chromium VI free: compliant with ROHS, WEEE and ELV Environmental Directives
- Clamping ranges to DIN 3017: 8 16 mm up to 140 160 mm
- Larger diameters on demand