

## Chainguard 550

**High temperature, graphited, EP chain and conveyor lubricant.**

**For the lubrication of conveyor chains and bearings in high temperature environments where the risk of product contamination by the lubricant cannot be tolerated. For example, bakery oven chains, or where temperatures are too high for wet lubricants to be used.**

### Features

- Temperature range: moist film –10°C to 180°C, Dry film up to 550°C
- Good EP and anti-wear performance
- Dry film (above 180°C) - Does not attract dust/dirt
- Excellent penetration ( must be applied below 120°C)

### Directions for Use

- ROCOL CHAIN GUARD 550 is a heavy duty lubricant designed for manual application by pressure oilcan
- It can also be brushed onto the chain, after the removal of any heavy deposits of dirt or grime.
- It should be applied to a cool chain (less than 120°C) to ensure adequate penetration before evaporation of the base fluid.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

## Chainguard 550

<b>Appearance</b>	Dark grey liquid
<b>Base type</b>	Poly alkylene glycol
<b>Performance additives</b>	Graphite
<b>Graphite content</b>	15%
<b>Graphite particle size</b>	95% less than 10 micron
<b>Temperature range</b>	
<b>Moist film</b>	-10°C to 180°C
<b>Dry film</b>	180°C to 550°C
<b>Base fluid viscosity at 40°C</b>	200cSt
<b>Base fluid viscosity at 100°C</b>	37 cSt
<b>Specific gravity</b>	1.1
<b>Storage</b>	Storage temperature should be controlled to between 1 and 40°C.
<b>Pack sizes – Part Codes</b>	5L – p/c 22076
	20L – p/c 22075

T +44 (0) 113 232 2600  
 F +44 (0) 113 232 2740  
 E customer-service@rocol.com  
 www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001  
 Certificate No. FM 12448



BS EN ISO 14001  
 Certificate No. EMS 67596



OHSAS 18001  
 Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.